

A photograph of two rock climbers on a steep, rocky cliff face. The climber in the foreground is wearing a yellow jacket and a yellow helmet, and is pulling a rope. The climber in the background is wearing a red jacket and a yellow helmet. The sun is low in the sky, creating a bright glow and long shadows.

CoastLine

CORDAGE GROUP

Bulwark Safety X Kernmantle Static Safety Rope

- Superior strength with low elongation
- NAFTA parallel twisted nylon core for superior strength with a HTP 9.6 grams per denier 32 carrier outer sheath
- Soft and supple with excellent abrasion elements.



CoastLineGroup.ca  



Bulwark Safety x
STRENGTH WHEN YOU NEED IT

Bulwark Safety X

Kernmantle Static Safety Rope



- Balanced-Ply non-rotational inner core and outer sheath (32 Carrier)
- Excellent grip cover
- Core: 100% nylon 6.6 (Polyamide)
- Cover: 100% High Tenacity Polyester
- Low Elasticity (2.0% @ 300lbF. - 3.9% @ 600LbF. - 5.8% @ 1000 LbF.)
- Excellent UV and abrasion resistance
- Specific gravity: 1.38 (sinks in water)
- Melting point 482°F (250°C)
- Custom lengths available upon request
- UL certified to NFPA 1983-2017 Technical Use
- 5:1 recommended working load
- Good resistance to chemicals

We are an SGS certified ISO:9001-2015 company. All employees of CCG are educated in the following standards of cordage manufacturing.



DIAMETER		WEIGHT		MINIMUM TENSILE STRENGTH		RECOMMENDED WORKING LOAD	
mm	inches	Kg/100m	llbs/100ft	Kg	llbs	Kg	llbs
8	5/16	5.8	4.0	2,177	4,800	435	960
10	3/8	6.7	4.6	2,622	5,781	524	1,156
11	7/16	8.2	5.6	3,028	6,676	605	1,335
12	1/2	9.8	6.7	3,910	8,621	782	1,724
16	5/8	11.9	8.0	5,907	12,997	1,032	2,270



COASTLINE Ropes Manufactured by CoastLine Cordage Group. © CoastLine Cordage Group.

CoastLine
CORDAGE GROUP

380 Bluewater Road, Bedford
Nova Scotia, Canada B4B 1J3

CoastLineGroup.ca
Tel 902-835-2253 | Fax 902-404-2567