



CoastLine

CORDAGE GROUP

Bulwark Safety X Semi-Static Kernmantle Safety Rope

- Superior strength with low elongation
- Parallel twisted nylon core for superior strength with a HTP 9.6 grams per denier 32 carrier outer sheath
- Soft and supple with excellent abrasion elements



CoastLineGroup.ca  



Bulwark Safety x
STRENGTH WHEN YOU NEED IT



Semi-Static Kernmantle Safety Rope

- Balanced-Ply non-rotational inner core and outer sheath (32 Carrier)
- Excellent grip cover
- Core: 100% nylon 6.6 (Polyamide)
- Cover: 100% High Tenacity Polyester
- Low Elasticity (2.0% @ 300lbF. - 3.9% @ 600LbF. - 5.8% @ 1000 LbF.)
Based on 11mm/7/16" rope diameter
- Excellent UV and abrasion resistance
- Specific gravity: 1.38 (sinks in water)
- Melting point 482°F (250°C)
- Custom lengths available upon request
- UL certified to NFPA 1983-2017 Technical/General Use
- Good resistance to chemicals

We are an SGS certified ISO:9001-2015 company. All employees of CCG are educated in the following standards of cordage manufacturing.



DIAMETER		WEIGHT		MINIMUM TENSILE STRENGTH	
mm	inches	Kg/100m	lbs/100ft	Kg	lbs
9.5	3/8	6.7	4.6	2,893	6,379
11	7/16	8.2	5.6	3,762	8,294
12.5	1/2	9.8	6.7	4,956	10,927



COASTLINE Ropes Manufactured by CoastLine Cordage Group. © CoastLine Cordage Group.