

CoastLine

CORDAGE GROUP

Bulwark Safety X Kernmantle Static Safety Rope

- Superior strength with low elongation
- NAFTA parallel twisted nylon core for superior strength with a HTP 9.6 grams per denier 32 carrier outer sheath
- Soft and supple with excellent abrasion elements.



Bulwark Safety X Kernmantle Static Safety Rope



- Balanced-Ply non-rotational inner core and outer sheath (32 Carrier)
- Excellent grip cover
- Core: 100% nylon 6.6 (Polyamide)
- Cover: 100% High Tenacity Polyester
- Low Elasticity (2.0% @ 300lbf. - 3.9% @ 600lbf. - 5.8% @ 1000 Lbf.)
- Excellent UV and abrasion resistance
- Specific gravity: 1.38 (sinks in water)
- Melting point 482°F (250°C)
- Custom lengths available upon request
- UL certified to NFPA 1983-2017 Technical Use
- 5:1 recommended working load
- Good resistance to chemicals

We are an SGS certified ISO:9001-2015 company. All employees of CCG are educated in the following standards of cordage manufacturing.



DIAMETER		WEIGHT		MINIMUM TENSILE STRENGTH		RECOMMENDED WORKING LOAD	
mm	inches	Kg/100m	lbs/100ft	Kg	lbs	Kg	lbs
8	5/16	5.8	4.0	2,177	4,800	435	960
10	3/8	6.7	4.6	2,622	5,781	524	1,156
11	7/16	8.2	5.6	3,028	6,676	605	1,335
12	1/2	9.8	6.7	3,910	8,621	782	1,724



COASTLINE Ropes Manufactured by CoastLine Group. © CoastLine Group.

CoastLine
CORDAGE GROUP

380 Bluewater Road, Bedford
Nova Scotia, Canada B4B 1H1

CoastLineGroup.ca
Tel 902-835-2253 | Fax 902-404-2567