

Index

Product Features	AWN-2
Elevations	AWN-4
Section Details: Interior Ovalo Profile (Aluminum Screen) Interior Ovalo Profile (Wood Stationary Screen) Interior Ovalo Profile (Roll Down Screen) Interior Ovalo Profile (Roll Down Screen c/w Push out) Interior Restoration Profile Option Interior Heritage Profile Option Interior Legacy Profile Option	AWN-5 AWN-6 AWN-7 AWN-8 AWN-9 AWN-10 AWN-11
Stacking & Mulling Details	AWN-13
Typical Wall Sections	AWN-14



Product Features

STANDARD FEATURES (Fixed unit):

- ~ Natural or prime time 2, eastern white pine (clear interior/finger joint exterior)
- ~ Frame construction design for 3 1/2" jambs
- ~ Clear insulated glass
- ~ Choice of black, grey or aluminum spacer bar
- ~ EM600 & 566 subsill

SPECIFICATIONS:

FRAME:

- ~ 11/16" thick X 3 1/2" width/base jamb in pine (or other wood species).
- ~ Jamb extension is 21/32" thick and is available up to 16"wide.
- ~ Frame is manufactured with Bulb weather-strip (white or beige).

SASH:

- ~ 1 5/8" thick in clear pine (or other wood species).
- ~ Interior profiling is ovalo or restoration profile.
- ~ Sash is manufactured with Polyflex weather-strip (white or black).

OPTIONS:

- ~ 2 1/4" thick sash in clear pine is also available (or other wood species).
- ~ Interior profiling on 2 1/4" thick sash is Heritage or Legacy profile.

HARDWARE:

Encore series from Truth – multipoint lock & escutcheon plate, roto-gear & foldaway handle.

- ~White (standard finish)
- ~ Coppertone (standard finish)
- ~ Oil rubbed bronze
- ~ Antique brass
- ~ Western pewter
- ~ Bright brass
- ~ Brush chrome
- ~ Bronze 03
- ~ Black
- ~ Brushed nickel
- ~ Bright chrome
- ~ Faux Oil Rub Bronze

Motorized hardware is also available. Sentry II operator and switch with optional remote control. Please contact a Norwood sales representative for more information and pricing.

SCREENS (aluminum) interior application:

- ~ White (standard)
- ~ Coppertone (standard)
- ~ Brown
- ~ Black
- ~ Beige
- ~ Ivory
- ~ Green
- ~ Mill finish
- ~ Norcoat finish

Aluminum screens are manufactured with 90 degree angled corners. (Note: Corners will not match Norcoat finish) Black, grey fiberglass mesh & Crystal Clear screen mesh available. Aluminum mesh is available upon request.



Product Features

SCREENS (wood) – interior application:

Wood screens are available as stationary or swinging in clear solid pine, finger joint pine or mahogany wood species. Other wood species are available upon request. Hinge & screen knob finishes are limited. Please contact a Norwood sales representative for more information.

SCREENS (roll down) – interior application:

- ~ Roll down screens available in all wood species.
- \sim Minimum 6 9/16" jamb and custom stiles & rails are required for this screen application.
- ~ Roll down screens add 7/8" to RO height.
- ~ Norwood recommends the use of a minimum 2 1/2" wide casing for this application

GRILLES:

SIMULATED DIVIDED LITE (SDL):

Exterior sdl available in putty & ovalo

- ~ 5/8"
- ~ 3/4" (putty only)
- ~ 7/8"
- ~ 1 1/4" ~ 1 3/4"
- ~ 1 3/4 ~ 2"
- ~ 2 1/4"

Interior sdl available in ovalo & restoration

- ~ 5/8"
- ~ 3/4" (restoration only)
- ~ 7/8"
- ~ 1 1/4"
- ~ 1 3/4"
- ~ 2" ~ 2 1/4"

TRUE DIVIDED LITE:

- ~ 15/16" (restoration & heritage only)
- ~ 1 1/4"
- ~ 1 3/4"
- ~ 2"
- ~ 2 1/4"

TDL is available with restoration & heritage profiles.

WOOD REMOVABLE GRILLES:

~ 7/8" ~ 1 1/4"

Wood removable grilles are complete with wood surround and only available in ovalo profile.

ALUMINUM GRILLES:

Aluminum grilles are located between the glass and are available rectangular. These grilles are available in white or white Georgian.

Pencil grilles are located between the glass and are available in 3/8" pewter or brass.


LEAD OVERLAY:

- ~ 1/4"
- ~ 3/8"
- ~ 1/2"

Lead overlay can be applied to one or multiple faces of glass, however, cannot be applied to the low-e surface. Lead overlay is available in patina or silver lead. Custom patterns are available upon request.



Elevations




Notes:


R.S.O. for additional combinations equals the sum of the unit size widths plus 1" and the sum of the unit heights plus 1 1/4".

M.O. for additional combinations equals the sum of the unit size widths or heights plus 3 5/16".

R.S.O. for stacked combinations mulled two or more wide and over 84" in width or height, it is recommended to add 11/16" filler for each stacked layer in height.



Suggested Awning combinations:




FIXED	FIXED
AWNING	AWNING


AWNING	
FIXED	

AWNING	AWNING
FIXED	FIXED
FIXED	FIXED




Section Details - Aluminum Screen








Section Details - Wood Stationary Screen






Section Details - Roll Down Screen



Awn-7 2012




Section Details - Roll Down Screen c/w Push out Hardware









Section Details - Restoration Profile Option








Section Details - Heritage Profile Option







Awn-10 2012




Section Details - Legacy Profile Option








Stack Details







Mull Details



TRANSOM / AWNING MULL 3 9/16" JAMB




3 9/16" JAMB C/W FILLER






Wall Section Detail





Wall Section Detail



AWNING - TYPICAL WALL SECTION DETAIL