

Mini CO₂TM

MINI CO₂ SUBMERSIBLE pCO₂ SENSOR

The Mini CO₂TM instrument uses infrared detection to measure the partial pressure of CO₂ gas dissolved in liquids. With pCO₂ ranges from 0-2000 ppm up to 0-100%, the Mini CO₂ provides the versatility needed for any application.

Mini CO₂TM submersible instruments are compact, lightweight, plug and play sensors. The instrument also measures total dissolved gas pressure (TDGP), a useful parameter for many applications and data correction.

With housing options rated to 6000 dbar of hydrostatic pressure, and resistance to most corrosive liquids, the Mini CO₂ can provide reliable dissolved carbon dioxide data for many applications. Flow-through and in-line adapters are also available for simple and effective industrial solutions.

For specialized applications, Pro-Oceanus can provide custom solutions to suit any need.



PRO
OCEANUS

Dissolved Gas Sensors

FEATURES

- Low power consumption
- Compact size
- Optional internal or external battery power
- Easy integration
- Large selection of concentration ranges
- Digital option comes with internal data logger and controller with 2GB flash memory

pCO₂ SENSOR APPLICATIONS

- Aquaculture monitoring of dissolved CO₂ for fish and shellfish health
- Coastal zone CO₂ fluxes
- Algae to fuel bioreactor feedback control
- Groundwater and wellwater monitoring
- Carbon budget studies for lakes and rivers
- Carbon capture storage monitoring of aquifer and surface water levels of pCO₂
- Wastewater greenhouse gas emissions
- Ocean glider and profiler missions

Mini CO₂™

SENSOR SPECIFICATIONS

Sensor Performance

CO₂ Measurement Ranges 0-2000 ppm CO₂; by volume
*other ranges available
0-5000 ppm
0-1% (10,000 ppm)
0-100%

Total Dissolved Gas Pressure 0-2 bar

Accuracy 3%

pCO₂ ± 2% of max range

TDGP ± 1%

Equilibration time (t₆₃) 3 minutes

Resolution 0.1% of max range

Physical

Length 28 cm (11 in)

Diameter 5.3 cm (2.1 in)

Weight Air: 0.53 kg (1.2 lbs)
Water: -0.06 kg (-0.1 lbs)

Housing Material Acetal Plastic / Titanium

Depth Rating 0 - 600 m (Plastic)
Up to 6000 m (Titanium)

Water Temperature -2° to 35° C

Electrical

Input voltage Digital: 7-24 VDC
Analog: 12-24 VDC

Power consumption Digital: 0.45 W (35 mA @ 12 VDC)
Analog: 0.6 W - 0.9 W (55 mA - 75 mA @ 12 VDC)

Data output Digital: RS-232, ASCII CSV
Analog: 0-5 V or 4-20mA

Sample rate 2 seconds (variable rate with logger/controller)

Optional Accessories

Titanium housings

Rated up to 6000 m depth

Internal battery power

External battery pack

19, 38 or 76 Amp-hour capacity

Water-pumped head

Reduce biofouling and improve response rate

Mooring cage or frame with instrument brackets

Pigtail Cables with Locking Sleeves

5, 10, 25, 50 meters, or longer



Water-Pumped Head Accessory



Pigtail Cable with Locking Sleeve



Copper Antifouling Shield