Solu-Blu™ GEN2 CH_4

DATA SHEET



SOLU-BLU™ GEN2 SUBMERSIBLE CH_4 SENSOR

The Solu-Blu™ GEN2 series of instruments are the next generation of dissolved gas monitoring. With a compact form and updated 6-pin micro series bulkhead connector, Solu-Blu GEN2 are designed to make dissolved gas measurements easier across research, aquaculture, and industrial applications while maintaining long-term reliability.

Built for durability, the Solu-Blu GEN2 CH_4 can be used for long-term continuous in-situ monitoring in numerous environments to provide reliable dissolved methane data. The probe provides fully temperature and pressure compensated data. Flow-through and in-line adapters are also available as custom options for simple and effective integration solutions.

FEATURES

- Low power
- Compact size
- Easy integration
- Durable
- Multiple output options
- Many concentration ranges

APPLICATIONS

- Dissolved methane levels for hydrofracturing
- Groundwater and well water monitoring
- Offshore oil and gas leak detection
- Wastewater greenhouse gas emissions
- Landfill leachate methane monitoring
- pCH_4 production in fermentation bioreactors

PRO OCEANUS Dissolved Gas Sensors
sales@pro-oceanus.com | +1 902-530-3550 | pro-oceanus.com

SENSOR SPECIFICATIONS

Sensor Performance


pCH_4 Measurement Ranges *other ranges available	0-10,000 µatm (0-1% CH_4; by volume) 0-10% v/v (0-3 mg/L) 0-100% v/v (0-30 mg/L)
Accuracy	±3% of max range
Resolution	0.1% of max range
Equilibration rate (t_{63})	~10 minutes

Electrical Parameters

Input voltage	8-24 VDC
Data output options	1. RS-232 CSV ASCII 2. RS-485 CSV ASCII or MODBUS 3. Analog 0-5 VDC 4. Analog 4-20 mA
Sample rate	1 second (variable with logger/controller)

Physical Parameters

Weight (Plastic)	Air: 0.4 kg (0.9 lbs) Water: 0 kg (0 lbs)
Housing	Plastic or Titanium
Depth Rating	Plastic: 0-600 meters Titanium: 0-6000 meters
Water Temperature	-2° to 35° C



Optional Accessories

Power/Communications Box
Allows for direct connection to computer and wall power outlet for plug and play operation

Water-Pumped Interface Head
Reduces biofouling and improves response rate

Pigtail Cables with Locking Sleeves
2, 5, 10, 20, 30, 50 meters or longer

Internal Battery power

Mooring cage or frame with instrument brackets

External Battery Pack

Scan me to learn more about the Pro-Oceanus Solu-Blu GEN2 Sensors

PRO OCEANUS Dissolved Gas Sensors

80 Pleasant Street,
Bridgewater, Nova Scotia
Canada B4V 1N1

sales@pro-oceanus.com
+1 902-530-3550
pro-oceanus.com