

Garage Exhaust Hose

A non-crushable heavy duty exhaust hose made of specially compounded rubber to resist heat, aging, gasoline exhaust and oil. Individual lengths are easily interconnected. Use metal transitions to lower exhaust temperatures to acceptable levels.



Ventilation pour station

Un boyau très résistant en caoutchouc spécialement composé pour résister la chaleur, l'âge, les émanations d'échappement d'essence et le pétrole. La longueur individuelle est facilement connectée. Utilisez les transitions en métal pour diminuer les températures d'échappement aux niveaux acceptables.

ID (inch)	WT/11ft (lbs)	Heat Resistance	Part Number
2"	6.2	up to 375°F	2" GARAGE
2-1/2"	7.0	up to 375°F	2-1/2" GARAGE
3"	9.4	up to 375°F	3" GARAGE
4"	16.0	up to 375°F	4" GARAGE
5"	24.5	up to 375°F	5" GARAGE
6"	25.9	up to 375°F	6" GARAGE*

* This hose is to be used only when there is no load on engine.

* Ce boyau doit être utilisé seulement quand il n'y a aucun chargement sur le moteur.

Universal Adapter



Rubber - easily adjusts with special fastener to fit tailpipes of most cars. 2-1/2" & 3"

Diesel Elbow Adapter




Aluminum - for diesel stacks. 4" connections on each end.

Door Port



Aluminum door port allows hose to be vented through the door.

Tail Pipe Adapter



This adapter will fit a tailpipe up to 3". Fits hoses sized 3" and 4". Comes with hook and chain.

Rubber Elbow Adapter



Rubber elbow connects two hoses for overhead pulley systems. 3" connection on each end.

CertTracker®
A virtual lifeline to safety 

100% web based certificate tracking system that provides our customers with the ability to easily access their current and past inspection certificates.



* May not be stock item / May require special order