

Sewer Cleaning Hose



Cover: Orange / Blue urethane.
 Reinforcement: Single high tensile polyester braid.
 Tube: Yellow Polyolefin.
 Applications: Used for flushing sewer lines.
 Manufactured in accordance with WEMI specifications.
 Temp Range: -40°C to 122°C (-40°F to 250°F)
 Standard Length: 500 & 600ft



Boyau de nettoyage d'égout

Couvert: Urethane orange / bleu.
 Renfort: Un pli de fibres polyester.
 Tube: Polyolefin jaune.
 Applications: Utilisé pour rincer des lignes d'égout. Le boyau est fabriqué en conformité de WEMI.
 Température: -40°C to 122°C (-40°F to 250°F)
 Emballage: 500 et 600'

ID (inch)	OD (inch)	WP (PSI)	Burst PSI	WT (lb/cft)	Length ft	Part Number
1"	1.46"	2500	6250	.40	500	SC16-500
1"	1.46"	2500	6250	.40	600	SC16-600*
1"	1.48"	3000	7500	.41	500	S916-500*
1"	1.48"	3000	7500	.41	600	S916-600*

Only use approved sewer flushing hose couplings.
 Utiliser seulement les raccord approuvés pour les boyau de nettoyage d'égout.

Paint Spray Hose



Cover: Black smooth oil & abrasion resistant rubber.
 Reinforcement: High tensile synthetic textile.
 Tube: Solvent resistant thermoplastic blend.
 Applications: Paint spray application involving most common solvents such as lacquer thinner, turpentine and duco.
 Temp Range: -40°C to 52°C (-40°F to 125°F)
 Standard Length: multiples of 25ft



Boyau à peinture

Couvert: Caoutchouc synthétiques noir, résistant aux abrasif et les huiles.
 Renfort: Plis multiples de fibres synthétiques.
 Tube: Thermoplastique résistant aux produits chimiques et aux solvants.
 Applications: Peinture au pistolet. Utilisation avec des solvants.
 Température: -40°C to 52°C (-40°F to 125°F)
 Emballage: Multiples de 25'

ID (inch)	OD (inch)	WP (PSI)	WT (lb/cft)	Part Number
1/4"	0.50"	175	7.2	1/4" PAINT
3/8"	0.68"	175	12.0	3/8" PAINT
1/2"	0.97"	175	18.7	1/2" PAINT *
3/4"	1.19"	150	19.3	3/4" PAINT *

Agricultural Spray Hose



Cover: Ribbed PVC.
 Reinforcement: High tensile yarn.
 Tube: Black PVC/ polyurethane blend.
 Applications: For spraying or transferring of aqueous or petroleum based herbicides and insecticides, such as Lasso. Cover is pin-pricked to vent vapour and prevent ballooning.
 Temp Range: -10°C to 70°C (15°F to 160°F)
 Standard Length: 300ft reels



Vaporisation

Couvert: PVC épingle.
 Renfort: Plis multiples de fibres synthétiques.
 Tube: PVC / polyurethane noir.
 Applications: Vaporisation de produits chimiques en solution, insecticides, herbicides et le Monsanto "Lasso".
 Température: -10°C to 70°C (15°F to 158°F)
 Emballage: bobine de 300'

ID (inch)	OD (inch)	WP (PSI)	WT (lb/cft)	Part Number	Alt Part #
3/8"	0.63"	300	12	3/8" AG-200*	A1628-06
1/2"	0.77"	300	16	1/2" AG-200*	A1628-08
3/4"	1.06"	200	27	3/4" AG-200*	A1628-12
1"	1.31"	200	34	1" AG-200*	A1628-16
3/8"	0.65"	600	13.5	3/8" AG-600	A1661-06
1/2"	0.79"	600	22	1/2" AG-600	A1661-08
3/4"	1.03"	600	35	3/4" AG-600	A1661-12
3/8"	0.65"	800	13.5	3/8" AG-800	A1687-06
1/2"	0.85"	800	22.5	1/2" AG-800	A1687-08
3/4"	1.03"	800	35	3/4" AG-800	A1687-12

* May not be stock item / May require special order