

Hot Water Wash Up



Cover: Smooth white EPDM.
 Reinforcement: Four spiral polyester yarn.
 Tube: Black heat resistant EPDM
 Applications: For general clean-up and hot water service in dairies, meat packing houses, creameries, food processing and bottling plants.
 Temp Range: -40°C to 93°C (-40°F to 200°F)
 Standard Length: 50ft (max 700ft reels)



Couvert: Caouthouc EPDM blanc.
 Renfort: Quatre spiral de polyester.
 Tube: Caouthouc EPDM noir
 Applications: Pour lavage général dans l'industrie alimentaire. Pas convenable pour la vapeur.
 Température: -40°C to 93°C (-40°F to 200°F)
 Emballage: 50' (bobine 700')

ID (inch)	OD (inch)	WP (PSI)	WT (lb/cft)	Part Number
1/2"	0.94"	250	30	1/2" HOT WATER
3/4"	1.25"	250	51	3/4" HOT WATER

Super Hot Water Wash Up



Cover: White synthetic rubber heat and abrasion resistant.
 Reinforcement: Two layers of synthetic yarn, fungus and mould resistant.
 Tube: White heat resistant rubber
 Applications: Same as Hot water, but use of premium materials gives longer service life. Not for steam service.
 Temp Range: -40°C to 93°C (-40°F to 200°F)
 Standard Length: 50ft (max 100ft)



Lavage à l'eau très chaude

Couvert: Caouthouc EPDM blanc.
 Renfort: Deux plis de fibres synthétiques résistant aux mycètes et aux bactéries.
 Tube: Caouthouc EPDM noir
 Applications: Même comme ci-dessus, mais l'usage de materials de première quality donne la durée d'utilisation plus longues. Pas convenable pour la vapeur.
 Température: -40°C to 93°C (-40°F to 200°F)
 Emballage: 50' (max 100')

ID (inch)	OD (inch)	WP (PSI)	WT (lb/cft)	Part Number
1/2"	0.94"	150	33	1/2" SUPER HOT
3/4"	1.23"	150	50	3/4" SUPER HOT
1"	1.52"	150	70	1" SUPER HOT*

Pressure Wash Hose



Cover: Blue abrasion and heat resistant rubber.
 Reinforcement: One or two steel braids.
 Tube: Black heat and chemical resistant rubber
 Applications: Pressure washer hose in 3000psi and 5800psi. Comes with male NPT, male NPT swivel and strain reliefs.
 Temp Range: -40°C to 150°C (-40°F to 310°F)
 Standard Length: 50ft, 75 and 100ft (max 500ft)



Lavage à l'eau très chaude

Couvert: Caouthouc bleu, résistant à l'abrasion et la chaleur.
 Renfort: Un et deux brin d'acier
 Tube: Caouthouc noir qui résiste la chaleur et les produits chimiques
 Applications: Conçu pour laveuse à haute pression. Disponible en 3000psi and 5,800psi, avec mâle NPT et serre-câble chaque bout.
 Température: -40°C to 150°C (-40°F to 310°F)
 Emballage: 50', 75' et 100' (max 500')

ID (inch)	OD (inch)	WP (PSI)	WT (lb/cft)	Min Bend	Assbly Length	Part Number
1/4"	0.47"	3000	12	2.5"	50ft	AG1T-04x50K
3/8"	0.65"	3000	19	3.0"	50ft	AG1T-06x50BLUEK
3/8"	0.65"	3000	19	3.0"	100ft	AG1T-06x100BLUEK
3/8"	0.69"	5800	23	3.2"	50ft	AG2T-06x50K
3/8"	0.69"	5800	23	3.2"	100ft	AG2T-06x100K

* Peut ne pas être un article courant / Peut exiger commande spéciale