

Contramine Yellow Air



Cover: Yellow SBR,
Black Stripe 300psi
Blue Stripe 400psi
Red Stripe Wire Air

Reinforcement: Multiple layers of spiral cord

Tube: Black SBR, oil mist resistant

Applications: Standard air hose designed for rigorous conditions prevailing in mining and industrial work.

Temp Range: -40°C to 85°C (-40°F to 185°F)

Standard Length: 50ft / 100ft

Boyaux d'air contramine jaune

Couvert: SBR jaune,
Raure noire 300psi
Raure bleu 400psi
Raure rouge Wire Air

Renfort: Corde spirale

Tube: SBR noire, résistance moyenne à l'huile

Applications: Un boyau d'air conçu pour les conditions rigoureuses qu'on retrouve dans les mines et chantiers de construction.

Température: -40°C to 85°C (-40°F to 185°F)

Emballage: 50' / 100'

Air 300



ID (inch)	OD (inch)	WP (PSI)	WT (lb/cft)	Part Number
1/2"	0.91	300	25	1/2" AIR 300
3/4"	1.22	300	40	3/4" AIR 300
1"	1.46	300	50	1" AIR 300
1-1/4"	1.81	300	70	1-1/4" AIR 300
1-1/2"	2.06	300	90	1-1/2" AIR 300
2"	2.63	300	116	2" AIR 300
2-1/2"	3.13	300	155	2-1/2" AIR 300
3"	3.66	250	199	3" AIR 300
4"	4.68	250	270	4" AIR 300

Air 400



ID (inch)	OD (inch)	WP (PSI)	WT (lb/cft)	Part Number
1/2"	0.91	400	31	1/2" AIR 400
3/4"	1.22	400	41	3/4" AIR 400
1"	1.46	400	61	1" AIR 400
1-1/4"	1.81	400	81	1-1/4" AIR 400
1-1/2"	2.06	400	91	1-1/2" AIR 400
2"	2.63	400	120	2" AIR 400
2-1/2"	3.13	400	181	2-1/2" AIR 400 *
3"	3.66	400	237	3" AIR 400
4"	4.68	400	330	4" AIR 400

Wire Air



ID (inch)	OD (inch)	WP (PSI)	WT (lb/cft)	Part Number
1/2"	0.98	1000	42	1/2" WIRE AIR
3/4"	1.22	800	55	3/4" WIRE AIR
1"	1.50	650	81	1" WIRE AIR
1-1/4"	1.81	650	103	1-1/4" WIRE AIR
1-1/2"	2.05	650	140	1-1/2" WIRE AIR
2"	2.60	650	188	2" WIRE AIR
2-1/2"	3.13	600	257	2-1/2" WIRE AIR
3"	3.70	450	335	3" WIRE AIR *
4"	4.88	400	470	4" WIRE AIR *

* May not be stock item / May require special order

Jack Hammer Hose

Cover: Smooth yellow and cut resistant
 Reinforcement: Spiraled synthetic yard
 Tube: Black oil mist resistant
 Applications: A long length air hose for construction and general industry.
 Temp Range: -40°C to 82°C (-40°F to 180°F)
Standard Length: 50ft Multiples and 700ft reels



Boyaux d'air de marteau-piqueur

Couvert: SBR jaune,
 Renfort: Corde spirale
 Tube: SBR noire, résistance moyenne à l'huile
 Applications: Un boyaux d'air de grande longueur pour la construction et l'industrie.
 Température: -40°C to 82°C (-40°F to 180°F)
Emballage: 50' , bobine 700'

ID (inch)	OD (inch)	WP (PSI)	WT (lb/cft)	Part Number
1/2"	0.88	300	27	1/2" JACKHAMMER *
3/4"	1.16	300	37	3/4" JACKHAMMER
1"	1.22	300	54	1" JACKHAMMER *

Assembly - 3/4" JH12X50C 3/4x50' Jackhammer c/w Chicago

Tundra Air Hose

Cover: Low temp red or yellow PVC
 Reinforcement: Braided synthetic yarn
 Tube: Low temp red or yellow PVC
 Applications: A light weight very flexible and durable air hose, ideal for air tools
 Temp Range: -40°C to 65°C (-40°F to 150°F)
Standard Length: 50ft multiples and 500ft reels



Couvert: PVC jaune ou rouge
 Renfort: brin synthetic
 Tube: PVC jaune ou rouge
 Applications: Un boyaux léger et très flexible d'air durable, idéaux pour des outils d'air.
 Température: -40°C to 65°C (-40°F to 150°F)
Emballage: 50' , bobine 500'

ID (inch)	OD (inch)	WP (PSI)	WT (lb/cft)	Part Number
1/4"	0.500	300	8.0	1/4" TUNDRA AIR
3/8"	0.625	300	10.0	3/8" TUNDRA AIR
1/2"	0.781	300	15.0	1/2" TUNDRA AIR

Assembly
 TUNDRA-06X25 3/8 x 25' Yellow Tundra Air c/w 1/4" MNPT ends
 TUNDRA-06x50R 3/8 x 50' Red Tundra Air c/w 1/4" MNPT ends
 TUNDRA-06x50Y 3/8 x 50' Yellow Tundra Air c/w 1/4" MNPT ends
 TUNDRA-06x100 3/8 x 100' Yellow Tundra Air c/w 1/4" MNPT ends

Self Storing Air Hose

Construction: Orange - Nylon
 Blue - Urethane
 Applications: A light weight, self retracting air hose, ideal for shop air tool.
 Temp Range: -40°C to 77°C (-40°F to 170°F)

Construction: Orange - nylon
 bleu - polyurethane
 Applications: Un boyaux d'air rétractant, idéal pour l'outil de source d'air comprimé.
 Température: -40°C to 77°C (-40°F to 170°F)



OD (inch)	Length (ft)	WP (PSI)	WT (lb/ea)	Type of Fittings	Part Number
1/4" (orange)	12.5	250	-	1/4" M/M NPT	NSS04-12
1/4" (orange)	25	250	-	1/4" M/M NPT	NSS04-25
3/8" (orange)	12.5	200	-	3/8" M/M NPT	NSS06-12
3/8" (orange)	25	200	-	3/8" M/M NPT	NSS06-25
1/2" (orange)	12.5	150	-	1/2" M/M NPT	NSS08-12
1/2" (orange)	25	150	-	1/2" M/M NPT	NSS08-25
1/4" (blue)	15	125	0.6	1/4" M/M NPT	USS04-15
1/4" (blue)	25	125	0.9	1/4" M/M NPT	USS04-25
3/8" (blue)	15	100	1.1	1/4" M/M NPT	USS06-15
3/8" (blue)	25	100	1.9	1/4" M/M NPT	USS06-25

* Peut ne pas être un article courant / Peut exiger commande spéciale