

Ultra high efficiency DUCTED HEAT PUMPS

2, 2.5, 3 & 4 tons

INFINITE COMFORT SERIES

XLTH

FUJITSU

AIRSTAGE



Eligible for
grant up to
\$5,000**

Canada
**Greener
Homes
Grant**

**While grants
are available.








12 Year
WARRANTY
Compressor
& Parts*

FUJITSU GENERAL
AIRSTAGE
CONTRACTOR
ELITE

*Applies when properly registered
AND installed by a Fujitsu
Elite Contractor in a residence.


THE LATEST IN INNOVATION

In a market that moves quickly, Fujitsu strives to stay ahead of the curve with a focus on product innovation that delivers. Leveraging cutting-edge Inverter technology, the newest system combines elements of the revolutionary side discharge outdoor unit with a standard modular indoor unit; all while still providing the same quiet, space saving, high efficiency system you know. Fujitsu is proud to present the **Infinite Comfort Series**, providing comfort without compromise.

SYSTEM	24LUAS1	30LUAS1	36LMAS1	48LMAS1	30LUAH1M	36LMAH1M	48LMAH1M
					XLTH	XLTH	XLTH
							
Indoor unit	AMUG24LMAS	AMUG30LMAS	AMUG36LMAS	AMUG48LMAS	AMUG30LMAS	AMUG36LMAS	AMUG48LMAS
Outdoor unit	AOUH24LUAS1	AOUH30LUAS1	AOUG36LMAS1	AOUG48LMAS1	AOUH30LUAH1	AOUH36LMAH1	AOUH48LMAH1

SUPERIOR HEATING PERFORMANCE

Whether it's the LMAS1 system or the XLTH model, the performance compared to a standard heat pump is 41% to 67% higher, even though outdoor units have a small footprint and very low noise levels.



Reliability you can count on


At Fujitsu, reliability means maintaining a consistent track record of product excellence. That's why 99.9% of Fujitsu customers have avoided replacing their system during its lifespan. Fujitsu's quality control standards are backed by four decades of HVAC experience and state-of-the-art testing technologies. This rigorous testing ensures that heating and cooling systems function as intended: with unrivalled efficiency and reliability. When it comes to staying comfortable in harsh conditions, trust Fujitsu to have your back.

Indoor unit features

- High static pressure, up to 1.0 inWG
- Indoor sound levels as low as 23 dBA
- Adaptive fan motor control - optimum indoor comfort
- Minimum clearance on three sides only 21 inch clearance on the front for service
- Downflow and horizontal right kits provided with each AHU at no additional cost
- Factory provided and field installed electric heat kit, manufactured by Fujitsu - up to 15.5 kW (optional)

Outdoor unit features

- Fully communicating heat pump with conventional multiposition air handler. Ideal solution for installations with limited space.
- Variable speed Inverter-driven compressor for optimum system operation and comfort
- High efficiency DC motor

	Conventional System	Fujitsu System
Noise Level	75 dBA	53 dBA
Footprint		



Smart device control (optional)

Wi-Fi compatible systems can be controlled from anywhere using the AIRSTAGE Mobile app on a mobile device, or smart home devices such as Amazon Alexa or Google Home.

Touch Panel Wired Remote Controls (optional)* UTYRVRU & UTYRNRUZ5

User friendly operation with high-definition touch screen

- Built-in temperature sensor
- Built-in weekly/daily timer
- Backlight enables easy operation in a darkened room
- Room temperature display
- Temperature set point limitation
- Multi-language
- Bluetooth app for install setup
- Custom logo import and display
- Blends with your decor, both residential and commercial

Optimum start function

- Provides configurable operation start to get the space to set temperature before scheduled time

Accurate and comfortable control

- Built-in air temperature sensor for accurate control and display of indoor air temperature

Kagami UTYRVRU	Touch Panel UTYRNRUZ5
-------------------	--------------------------

- | | |
|---|---|
| ✓ | ✓ |
| ✓ | ✓ |
| ✓ | ✓ |
| ✓ | ✓ |
| ✓ | ✓ |
| ✓ | ✓ |
| ✓ | ✓ |
| ✓ | ✓ |
| ✓ | ✗ |
| ✓ | ✗ |
| ✓ | ✗ |
| ✓ | ✓ |
| ✓ | ✓ |



UTYRVRU



UTYRNRUZ5

*Other optional accessories available, all sold separately.



Communicating zoning system (optional)

Benefits & features

- An Airzone system can provide optimum airflow into each zone, thus reducing excess equipment capacity
- Provides ideal temperature control of each zone
- Built in communication gateways maximize Fujitsu heat pump Inverter efficiency
- Adjustable minimum and maximum damper positions
- Control of optional auxiliary heat of the ducted, zoned unit
- Blueface principal controller provides simple, single point temperature management of ALL zones
- Wired and wireless dampers available.

Performance & warranty

Fujitsu heat pumps are designed to last and deliver unmatched performance year after year. This is why Fujitsu equipment is backed by one of the best warranties in the industry. Not only that, your Fujitsu dealer is supported by The Master Group, the largest, independently owned HVAC-R distributor in Canada with a 70 year history of providing extensive inventory, exceptional customer service, and unmatched technical expertise.

			XLTH -26°C							
			2 ton	2.5 ton	3 ton	4 ton	2.5 ton	3 ton	4 ton	
Model	Indoor Unit		AMUG24LMAS**	AMUG30LMAS**	AMUG36LMAS**	AMUG48LMAS	AMUG30LMAS**	AMUG36LMAS**	AMUG48LMAS**	
	Outdoor Unit		AOUH24LUAS1	AOUH30LUAS1	AOUH36LMAS1	AOUH48LMAS1	AOUH30LUAH1	AOUH36LMAH1	AOUH48LMAH1	
	AHRI number		211078835	211078838	205123809	205123810	207657376	207657377	207657378	
Power Source	Voltage/Frequency/Phase	V / Ø / Hz	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	
	Available Voltage Range	V	187 - 253	187 - 253	187 - 253	187 - 253	187 - 253	187 - 253	187 - 253	
	Supply Intake	-	Outdoor Unit	Outdoor Unit	Outdoor Unit	Outdoor Unit	Outdoor Unit	Outdoor Unit	Outdoor Unit	
Cooling performance	Rated Capacity		BTU/h	24,000	30,000	36,000	45,600	28,600	33,000	45,500
	Rated Power Use		KW	2.05	3.00	3.36	5.56	2.44	3	5.17
	EER2		BTU/hW	11.7	10.0	10.7	8.2	11.7	11	8.8
	SEER2		BTU/hW	18.8	18.5	17.1	16.2	18.8	17.1	16.6
	Airflow	High	CFM	800	870	1,200	1,640	870	1,200	1,640
		Medium	CFM	670	730	740	1,020	730	740	1,020
		Low	CFM	590	590	590	820	590	590	820
		Quiet	CFM	310	310	490	590	310	490	590
	Sound	IDU Sound H/M/L/Q	dB(A)	40/34/32/26	42/37/33/28	41/30/27/24	48/36/31/25	42/37/33/28	41/30/27/24	48/36/31/25
		Outdoor Unit (Rated)	dB(A)	52	53	53	54	52	52	54
Heating performance	Rated Capacity		BTU/h	27,000	32,000	42,000	53,000	32,000	38,000	51,000
	Rated Power Use		KW	2.31	2.82	3.85	5.43	2.71	2.96	4.22
	COP2		kW/kW	3.42	3.32	3.2	2.86	3.46	3.76	3.62
	HSPF2 region 5 (region 4)		BTU/hW	8 (10)	7.6 (9.5)	7.3 (8.8)	7.2 (9.2)	8.1 (9.7)	8.6 (10.4)	8.1 (10)
	Btu max. at 8°C (47°F)			32,000	38,000	52,000	54,000	39,000	52,000	55,000
	Btu max. at -8°C (17°F)			25,600	30,200	38,000	40,200	34,730	44,880	51,000
	Btu max. at -15°C (5°F)			23,000	27,000	32,900	34,200	33,000	42,000	51,000
	Btu max. at -26°C (-15°F)			N/A	N/A	N/A	N/A	26,000	32,000	39,000
	Airflow	High	CFM	800	870	1,200	1,640	870	1,200	1,640
		Medium	CFM	670	730	740	1,020	730	740	1,020
Low		CFM	590	590	590	820	590	590	820	
Quiet		CFM	310	310	490	590	310	490	590	
Sound	IDU Sound H/M/L/Q	dB(A)	37/33/31/25	39/36/32/25	40/35/28/26	47/37/32/29	39/36/32/25	40/35/28/26	47/37/32/29	
	Outdoor Unit (Rated)	dB(A)	54	55	54	55	53	53	54	
Max. Circuit Breaker		A	20	25	40	40	35	40	45	
Static Pressure Range		inWG(Pa)	0.08-1.0 (20-250)	0.08-1.0 (20-250)	0.08-1.0 (20-250)	0.08-1.0 (20-250)	0.08-1.0 (20-250)	0.08-1.0 (20-250)	0.08-1.0 (20-250)	
Net. Dimensions	Indoor Unit	in. (mm)	42 1/2 x 21 x 21 11/16 (1,080 x 533 x 551)	42 1/2 x 21 x 21 11/16 (1,080 x 533 x 551)	57 x 21 x 21 11/16 (1,448 x 533 x 551)	57 x 21 x 21 11/16 (1,448 x 533 x 551)	42 1/2 x 21 x 21 11/16 (1,080 x 533 x 551)	57 x 21 x 21 11/16 (1,448 x 533 x 551)	57 x 21 x 21 11/16 (1,448 x 533 x 551)	
	Outdoor Unit	in. (mm)	31 x 37 x 12 5/8 (788 x 940 x 320)	39 5/16 x 37 x 12 5/8 (998 x 940 x 320)	39 5/16 x 38 3/16 x 14 9/16 (998 x 970 x 370)	39 5/16 x 38 3/16 x 14 9/16 (998 x 970 x 370)	39 5/16 x 38 3/16 x 14 9/16 (998x970x370)	52 1/2 x 38 3/16 x 14 9/16 (1,334 x 970 x 370)	52 1/2 x 38 3/16 x 14 9/16 (1,334 x 970 x 370)	
Net. Weight	Indoor Unit	lbs (kg)	104 (47)	104 (47)	132 (60)	132 (60)	104 (47)	132 (60)	132 (60)	
	Outdoor Unit	lbs (kg)	117 (53)	139 (63)	198 (90)	198 (90)	187 (85)	236 (107)	236 (107)	
Installation	Lineset Size Liquid - Gas	in.	3/8 - 5/8	3/8 - 5/8	3/8 - 5/8	3/8 - 5/8	3/8 - 5/8	3/8 - 5/8	3/8 - 5/8	
	Maximum Lineset Length	ft.	164	164	230	230	246	246	246	
	Pre-charge Lineset Length	ft.	66	66	98	98	98	98	98	
	Max. height difference	ft.	98	98	98	98	98	98	98	
Moisture removal		pints/h (L/h)	5.5 (2.6)	8.2 (3.9)	4.6 (2.2)	4.6 (2.2)	6.8 (3.2)	6.6 (3.1)	9.3 (4.4)	
Operation Range	Cooling	°C (°F)	-21~46 (-5~115)	-21~46 (-5~115)	-10~46 (14~115)	-10~46 (14~115)	-21~46 (-5~115)	-21~46 (-5~115)	-21~46 (-5~115)	
	Heating	°C (°F)	-21~24 (-5~75)	-21~24 (-5~75)	-20~24 (4~75)	-20~24 (4~75)	-26~24 (-15~75)	-26~24 (-15~75)	-26~24 (-15~75)	
Eligible for Greener Home Grant**			YES	YES	YES	YES	YES	YES	YES	

Authorized dealer



- Standard residential application warranty is 5-years on parts & 7-years on compressor. May be extended to 10-years parts & compressor if registered on the Fujitsu portal within 60 days of the installation date.
- 12-years parts & compressor warranty for Elite and Elite Plus contractors if registered on the Fujitsu portal within 60 days of the installation date.
- 5 & 10-year labour warranty plans available for purchase separately from third party (12-years for Elite dealers), ask your dealer for more details.

The Fujitsu logo is a registered trademark of Fujitsu Limited. AIRSTAGE logo and name is a trademark of Fujitsu General America, Inc. Other company and product names mentioned herein may be registered trademarks, trademarks or trade names of their respective owners. Specifications and design are subject to change without notice for future improvement. Actual products colors may be different from the colors shown in this printed material.

