

9,000 BTU MODELS

| | Fujitsu ASU/AOU9RLFW1 | Fujitsu ASU/AOU9RLS3 | Fujitsu ASU/AOU9RLS3H | mitsubishi MSZ/MUZFH09NAH | DAIKIN FTXS/RXS09LVJU | LG LAN/LAU09HYV | PANASONIC CS/CU-XE9PKUA |
|--|----------------------------|----------------------------|----------------------------|--|-----------------------------------|--|----------------------------|
| Nominal cooling BTU/h | 9,000 | 9,000 | 9,000 | 9,000 | 9,000 | 9,000 | 8,700 |
| Min. ~ Max. cooling BTU/h | 1,700-10,900 | 3,100-12,000 | 3,100-12,000 | 1,700-12,000 | 4,400-9,000 | 1,023-12,966 | 2,800-12,000 |
| Nominal heating BTU/h | 12,000 | 12,000 | 12,000 | 10,900 | 9,000 | 11,000 | 12,000 |
| Min. ~ Max. heating BTU/h | 1700-15000 | 3100-22000 | 3100-22000 | 1600-18000 | 4400-12000 | 1023-20472 | 3,000-18,000 |
| Heating capacity at -8°C (17°F) BTU/h | 8,660 | 16,600 | 16,600 | 12,200 | 7,570 | 11,935 | 10,600 |
| Heating operating range with BTU/h capacity | 5°F (-15°C) 6840 | -5°F (-21°C) 14000 | -15°F (-26°C) 11100 | -13°F (-25°C) 7300 | 5°F (-15°C) 5370 | -13°F (-25°C) 7920 | 5°F (-15°C) 11000 |
| Base heater | no | no | yes | optional | optional | no | no |
| SEER BTU/hW | 23 | 33 | 33 | 30.5 | 24.5 | 27.5 | 28.5 |
| EER clg/htg | 13.8 | 18 | 18 | 16.1 | 15.3 | 16.01 | 16.1 |
| HSPF BTU/hW IV region | 11 | 14.2 | 14 | 12.5 | 12.5 | 11.8 | 12.5 |
| COP at 17°F (-8.3°C) (kW/kW) | 3.95 | 5.33 | 5.33 | 4.5 | 4.46 | 4.6 | 3.52 |
| Air circ. CFM | 194-441 | 224-489 | 224-489 | 137-381 | 145-381 | 283-547 | 405 |
| Indoor noise level db(A) | 21-43 | 23-42 | 23-42 | 20-40 | 22-41 | 17-42 | 20-42 |
| Outdoor noise level db(A) | 48 | 42/47 | 42/47 | 48 | 47 | 45 | 48 |
| Warranty | 10 years parts & labour | 10 years parts & labour | 10 years parts & labour | 6 years parts, 10 years compressor* 6 years parts, 10 years compressor* & 6 years labour for certified dealer | 12 years parts, 6 years labour | 5 years parts, 7 years compressor* *7 years parts & labour or 10 years parts & labour available in option | 10 years parts & labour |

12,000 BTU MODELS

| | Fujitsu ASU/AOU12RLF1 | Fujitsu ASU/AOU12RLS3 | Fujitsu ASU/AOU12RLS3H | DAIKIN MSZ/MUZFH12NAH | DAIKIN FTXS/RXS12LVJU | DAIKIN FTXG/RXG12HVJU | LG LAN/LAU12HYV | PANASONIC CS/CU-XE12PKUA |
|--|----------------------------|----------------------------|----------------------------|--|-----------------------------------|-----------------------------------|--|-----------------------------|
| Nominal cooling BTU/h | 12,000 | 12,000 | 12,000 | 12,000 | 12,000 | 12,000 | 12,000 | 11,500 |
| Min. ~ Max. cooling BTU/h | 3,100-13,000 | 3,100-13,600 | 3,100-13,600 | 2,500-13,600 | 4,800-12,000 | 5,300-15,700 | 1,023-13785 | 2,800-14,000 |
| Nominal heating BTU/h | 16,000 | 16,000 | 16,000 | 13,600 | 14,400 | 16,000 | 13,600 | 13,800 |
| Min. ~ Max. heating BTU/h | 3,100-19,100 | 3,100-22,000 | 3,100-22,100 | 3,700-21,000 | 4,800-14,400 | 4,400-19,100 | 1,023-22,178 | 3,000-23,000 |
| Heating capacity at -8°C (17°F) BTU/h | 12,710 | 17,900 | 17,900 | 13,600 | 10,100 | 10,400 | 14,650 | 13,500 |
| Heating operating range with BTU/h capacity | 5°F (-15°C) 10,200 | -5°F (-21°C) 15,000 | -15°F (-26°C) 11,800 | -13°F (-25°C) 9,900 | 5°F (-15°C) 6,430 | 14°F (-10°C) 10,220 | -13°F (-25°C) 9,520 | 5°F (-15°C) 12,500 |
| Base heater | no | no | yes | optional | optional | optional | no | no |
| SEER BTU/hW | 22 | 29.3 | 29.3 | 26.1 | 23 | 21 | 25.5 | 25.5 |
| EER clg/htg | 12.5 | 15.2 | 15.2 | 13.8 | 12.8 | 12.9 | 14.12 | 14.35 |
| HSPF BTU/hW IV region | 11 | 14 | 13.8 | 11.5 | 12.5 | 10.55 | 11.5 | 12 |
| COP at 17°F (-8.3°C) (kW/kW) | 3.66 | 4.64 | 4.64 | 4.2 | 4.35 | 4.04 | 4.63 | 4.05 |
| Air circ. CFM | 194-441 | 224-489 | 224-489 | 137-398 | 155-403 | 272-470 | 283-547 | 530 |
| Indoor noise level db(A) | 21-43 | 23-42 | 23-42 | 20-40 | 22-41 | 22-41 | 17-42 | 20-42 |
| Outdoor noise level db(A) | 49 | 43/47 | 43/47 | 49 | 49 | 49 | 45 | 49 |
| Warranty | 10 years parts & labour | 10 years parts & labour | 10 years parts & labour | 6 years parts, 10 years compressor* 6 years parts, 10 years compressor* & 6 years labour for certified dealer | 12 years parts, 6 years labour | 12 years parts, 6 years labour | 5 years parts, 7 years compressor* *7 years parts & labour or 10 years parts & labour available in option | 10 years parts & labour |

15,000 BTU MODELS

| | Fujitsu ASU/AOU15RLS3 | Fujitsu ASU/AOU15RLS3H | mitsubishi MSZ/MUZFH15NAH | DAIKIN FTXS/RXS15LVJU | DAIKIN FTXG/RXG15HVJU |
|--|--------------------------|---------------------------|--|-----------------------------------|-----------------------------------|
| Nominal cooling BTU/h | 14,500 | 14,500 | 15,000 | 15,000 | 15,000 |
| Min. ~ Max. cooling BTU/h | 3,100-18,400 | 3,100-18,400 | 6,400-19,000 | 5,800-15,000 | 5,300-18,000 |
| Nominal heating BTU/h | 18,000 | 18,000 | 18,000 | 18,000 | 18,000 |
| Min. ~ Max. heating BTU/h | 3,100-23,900 | 3,100-23,900 | 5,150-24,000 | 5,800-18,000 | 4,400-21,200 |
| Heating capacity at -8°C (17°F) BTU/h | 22,200 | 22,200 | 18,000 | 11,900 | 11,100 |
| Heating operating range with BTU/h capacity | -5°F (-21°C) 18,600 | -15°F (-26°C) 16,300 | -13°F (-25°C) 14,600 | 5°F (-15°C) 7,840 | 14°F (-10°C) 11,510 |
| Base heater | no | yes | yes | optional | optional |
| SEER BTU/hW | 25.3 | 25.3 | 22 | 20.6 | 21 |
| EER clg/htg | 13.9 | 13.9 | 12.5 | 14.4 | 12.9 |
| HSPF BTU/hW IV region | 13.4 | 13.3 | 10.3 | 12.5 | 10.0 |
| COP at 17°F (-8.3°C) (kW/kW) | 4.59 | 4.59 | 4.06 | 4.0 | 3.99 |
| Air circ. CFM | 259-489 | 259-489 | 225-411 | 371-593 | 293-494 |
| Indoor noise level db(A) | 23-42 | 23-42 | 20-40 | 22-41 | 22-41 |
| Outdoor noise level db(A) | 49/50 | 49/50 | 51 | 62 | 50 |
| Warranty | 10 years parts & labour | 10 years parts & labour | 6 years parts, 10 years compressor* 6 years parts, 10 years compressor* & 6 years labour for certified dealer | 12 years parts, 6 years labour | 12 years parts, 6 years labour |