

# Product Spotlight

## GYLON EPIX™

The Perfect solution to imperfect flanges.

Style 3504 EPX Aluminosilicate Microsphere



Style 3510 EPX Barium Sulfate



Style 3500 EPX



#### INVENTORY SIMPLIFICATION

Offered in one universal thickness, 3/32" (2.4mm), eliminating the need to stock a variety of material thicknesses with different stress requirements. This translates to reduced inventory and better sheet utilization.

### IMPROVED LOAD RETENTION

GYLON EPIX™ features a hexagonal surface profile that provides the torque retention and blowout resistance of a thin gasket and the conformability of a thicker gasket.

#### TRUSTED MATERIALS

Made from the same PTFE material as standard GYLON® products it eliminates the need for most customers to qualify the new GYLON EPIX™ products.

- TTL has recently added GYLON EPIX<sup>™</sup> to our product line. GYLON EPIX<sup>™</sup> is a newly developed family of PTFE gaskets.
- Manufactured using a patented, profiled surface based on our proven Fawn, Off-White, and Blue GYLON® to create highly conformable materials for optimum sealing performance.

Contact your TTL Sales Representative to discuss how Gylon EPIX™ can service your industry.

Head Office: 902.468.5202 NL Office: 709.579.2801 Toll Free: 1.800.295.3365 www.ttlsupply.ca